

Reaching New Heights

DPM model offers options for double person baskets in our DU and DP series.



Conveniently positioned controls will allow the operator to be more effective when maneuvering their materials.



-35° Boom angle gives the operator the flexibility of ground level basket access for overall ease of use.



UP TO 52' WORKING HEIGHT



SPECIFICATIONS

DPM 47

Height to Bottom of Platform	47'
Working Height	52'
Side Reach	31' 6"
Approximate Stowed Travel Height	10' 5"
Platform Capacity (MH Models)	400#
Platform Capacity Using Jib (DU Model)	400#
Platform Capacity not Using Jib (DU Model)	550#
Platform Capacity (DP Model)	600#
Approximate Weight	4300#
Articulating Arm Travel	0 to 80
Main Boom Travel	-35 to 80
Extension Travel	120"

Minimum GVWR will change significantly depending on make of chassis and stabilizer option. Dur-A-Lift Inc. reserves the right to improve models and change specifications without notice or obligation. Dur-A-Lift equipment meets or exceeds all applicable ANSI Standards as of the date of manufacture.

STANDARD FEATURES

- Proportional Controls
- Lower Override Controls
- Engine Start/Stop from Basket
- Basket Access from Ground
- Compensated Upper Boom
- Insulated Cat "C" Extension Boom
- Hydraulic Basket Leveling
- Continuous Rotation
- Joystick and Lockout Controls

DPM-47 MH FEATURES

- Up to 1000# Jib and Winch
- Upper and Lower Winch Control
- 400# Basket Capacity
- 24" X 30" Fiberglass Basket
- 180° Basket Rotator

DPM-47 DP FEATURES

- 600# Basket Capacity
- 24" X 48" Fiberglass
- 180° Basket Rotator

DPM-47 DU FEATURES

- Up to 1000# Jib and Winch
- 550# Basket Capacity When Not Using Winch
- 400# Basket Capacity When Using Winch
- 24" X 42" Fiberglass
- 24" X 42" Aluminum Basket
- 100° Basket Rotator

Options

- High Electrical Resistant Controls
- Outriggers
- Basket Liner for Fiberglass Baskets
- Fiberglass Main and Articulating Booms
- Tool Circuits
- D.C. Backup System
- 180° Basket Rotator (DU)
- Aluminum Basket

This aerial lift is sold and serviced by:

DPM 47 Reach Diagram

